



COMFORT Unnapped Loop

Technical Information

Unnapped Loop
Base Material: Nylon 100%
Width: 20mm, 25mm, 38mm, 50mm
Width Tolerance: ±5%
Weight: 7.8g ± 0.5g/metre (25mm width)
Temperature Range: 0-60°C
Colour Fastness to Laundering: Grade 3+ (AATCC M61 2A)
Colour Fastness to Hot Water: Grade 3+ (CNS 1495 L3028)
Colour Fastness to Perspiration: Acid Grade 3+ / Alkali: Grade 3+ (ISO 105 E04)

Peel strength CNS 12649 L3227 - Standard Hook	Average:
After 1 opening & closing cycle	80+ g/cm

Shear strength CNS 12649 L3227 - Standard Hook	Average:
After 1 opening & closing cycle	0.75+ kg/cm ²

Tear strength ASTM D2261	Results:
	2 kg+

DISCLAIMER

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because HALCO Europe Ltd t/a CONNTEX cannot accept responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.

UK HEAD OFFICE Pioneer House, Beacon Road, Hereford HR2 6JF, UK | Tel: +44(0) 1432 842 020 | sales@conntex.com
EU HEAD OFFICE Kleinhülsen 11, 40721 Hilden, Germany | Tel: +49(0) 2103 78907 30 | kontakt@conntex.com

OTHER LOCATIONS: **FRANCE** **SPAIN** **ITALY** **POLAND** **USA** **AUSTRALIA**



Certificate Number 8158